

## Indicative declaration

Leca Danmark A/S  
 Randersvej 75, Hinge  
 DK-8940 Randers SV, Denmark  
 Phone: +45 87 61 02 01  
 Fax: +45 85 61 02 05  
 Web: www.leca.dk

Issued: 01-04-2017  
 Substitute for: 01-04-2016

Product name	<b>Leca® 0 - 4 (15-35-50)</b>		
Article number	<b>16 00 50 00</b>		
Composition of basic grades	(15--34-0--49--0)		
Indicative properties*	Limits	Typical value	
Aggregate size	<b>0,063 - 4 mm</b>		
Particle shape	<b>Round/cracked</b>		
Aggregate size distribution	Sieves	Passing	
	6,3 mm	100 - 100 %	<b>100 %</b>
	5,6 mm	100 - 100 %	<b>100 %</b>
	4 mm	95 - 100 %	<b>98 %</b>
	3,15 mm	80 - 90 %	<b>85 %</b>
	2 mm	55 - 65 %	<b>60 %</b>
	1 mm	35 - 50 %	<b>44 %</b>
	0,25 mm	20 - 30 %	<b>24 %</b>
0,063 mm	2 - 15 %	<b>7 %</b>	
Loose bulk density	300 - 410 kg/m <sup>3</sup>		
Chloride	max. 0,02 %		
Acid-soluble sulphate	max. 0,5 %		
Total sulphur	max. 0,32 %		

\* Properties are calculated from the basic grades of Leca® 0-0,5; Leca® 0,5-2,5; Leca® 0,5-2,5 round; Leca® 2-4 cracked and Leca® 2-4 round; all of which are CE marked according to EN 13055-1

