

## Indicative declaration

Leca Danmark A/S  
 Randersvej 75, Hinge  
 DK-8940 Randers SV, Denmark  
 Phone: +45 87 61 02 01  
 Fax: +45 85 61 02 05  
 Web: www.leca.dk

Issued: 01-04-2017  
 Substitute for: 01-05-2016

Product name	<b>Leca® 0 - 4 (18-42-40)</b>		
Article number	<b>16 00 40 00</b>		
Composition of basic grades	(18-42-0-41-0)		
Indicative properties*	Limits	Typical value	
Aggregate size	<b>0,063-4 mm</b>		
Particle shape	<b>Round/crushed</b>		
Aggregate size distribution	Sieves	Passing	
	6,3 mm	100 - 100 %	<b>100 %</b>
	5,6 mm	100 - 100 %	<b>100 %</b>
	4 mm	96 - 100 %	<b>98 %</b>
	3,15 mm	85 - 95 %	<b>88 %</b>
	2 mm	65 - 70 %	<b>68 %</b>
	1 mm	45 - 55 %	<b>50 %</b>
	0,25 mm	20 - 35 %	<b>27 %</b>
0,063 mm	3 - 15 %	<b>8 %</b>	
Loose bulk density	305 - 415 kg/m <sup>3</sup>		
Chloride	max. 0,02 %		
Acid-soluble sulphate	max. 0,5 %		
Total sulphur	max. 0,32 %		

\* Properties are calculated from the basic grades of Leca® 0-0,5; Leca® 0,5-2,5; Leca® 0,5-2,5 round; Leca® 2-4 cracked and Leca® 2-4 round; all of which are CE marked according to EN 13055-1

