

DECLARATION OF PERFORMANCE

in accordance with EU Construction Products Regulation (CPR) no 305/2011 and Commission Delegated Regulation (EU) No 574/2014

No. DoP_DK_16011000_EN 13055-2_UK_Ver2

- 1. Unique identification code of the product-type: 16011000_EN 13055-2 (Leca® 2-4 round)
- 2. Intended use/s:

Expanded clay lightweight aggregate for unbound and hydraulically bound applications in buildings, roads and civil engineering works

3. Manufacturer:

Leca Danmark A/S

Randersvej 75 DK-8940 Randers SV, Denmark

Phone: +45 87 61 02 01 Web: www.leca.dk

4. Authorised representative:

Leca Norge AS	Leca Sverige AB	Fibo ExClay Deutschland GmbH	Leca UK
Årensvegen 1	Box 6103	Rahdener Strasse 1	Regus House, Herons way
2009 Nordby,	580 06 Linköping	80 06 Linköping 21759 Lamstedt Chester Busin	
Norway	Sweden	Germany	Chester, CH4 9QR
			UK
Phone: +47 4148 7100	Phone +46 3186 7727	Phone +49 4773 896 0	Phone +44 844 3351 770
Web: www.leca.com	Web: www.leca.com	Web: www.leca.com	Web: www.leca.com

- 5. System/s of AVCP: System 4
- 6. Harmonised standard: EN 13055-2:2004



7. Declared performance/s:

Essential characteristics Loose bulk density		Performance 380 kg/m³ +/- 15 %	
Particle shape		Round	
Water absorption/	Water absorption	NPD	
suction	Water suction height	NPD	
Resistance to fragmentation/ crushing		NPD	
Percentage of crushed particles		NPD	
Volume stability		NPD	
Durability against freeze/thaw/weathering		Durable according to long term experience in	
		Nordic climate	
Composition/content	Chloride	< 0,02 %	
	Acid soluble sulfate	< 0,5 % SO ₃	
	Total sulfur	< 0,32 % S	
Cleanliness		NPD	
Release of heavy metals by leaching		NPD	
Release of other dangerous substances		NPD	

8. Appropriate Technical Documentation and/or Specific Technical Documentation:
Not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Operations Director Susanne Bay Jensen (name)

2021.02.03

Randers (place)



CE-marking



Leca Danmark A/S Randersvej 75 DK-8940 Randers SV

17

DoP_DK_ 16011000_EN 13055-2

EN 13055-2

16011000_EN 13055-2 Leca® 2-4 round

Intended use(s):

Expanded clay lightweight aggregate for unbound and hydraulically bound applications in buildings, roads and civil engineering works

Declared performance:

Particle shape: Round

Declaration of Performance and CE-marking can be found at www.leca.dk or sent on request.