



DECLARATION OF PERFORMANCE

in accordance with EU Construction Products Regulation (CPR) no 305/2011
and Commission Delegated Regulation (EU) No 574/2014

No. DoP_DK_16021000_EN 14063-1_UK_Ver2

- Unique identification code of the product-type:*
16021000_EN 14063-1, Leca® 4-10 rund, Leca® Medium
- Intended use/s:*
Expanded clay lightweight aggregate for in-situ formed thermal insulation of ground floors
- Manufacturer:*
Leca Danmark A/S
Randersvej 75
DK-8940 Randers SV,
Denmark
Phone: +45 87 61 02 01
Web: www.leca.dk
- Authorised representative:*

Leca Norge AS Årensvegen 1 2009 Nordby, Norway Phone: +47 4148 7100 Web: www.leca.com	Leca Sverige AB Box 6103 580 06 Linköping Sweden Phone +46 3186 7727 Web: www.leca.com	Fibo ExClay Deutschland GmbH Rahdener Strasse 1 21759 Lamstedt Germany Phone +49 4773 896 0 Web: www.leca.com	Leca UK Regus House, Herons way Chester Business Park Chester, CH4 9QR UK Phone +44 844 3351 770 Web: www.leca.com
---	--	---	---

- System/s of AVCP:*
System 3
- Harmonised standard:*
EN 14063-1:2004

Notified body/ies:
No. 1275 Danish Technological Institute (Thermal conductivity)



7. Declared performance/s:

Essential characteristics		Performance
Reaction to fire		Euroclass A1 (according Commission Decision 2000/605/EC)
Water permeability (water suction height)		< 75 mm
Release of dangerous substances		NPD
Thermal resistance	Thermal conductivity	0,095 W/mK
	Loose bulk density	305 kg/m ³ +/- 15 %
	Aggregate size	4 – 10 mm
Water vapour transmission		NPD
Compressive strenght		> 0,82 N/mm ²
Durability of reaction to fire against ageing/degradation		Does not change with time
Durability of thermal resistance against ageing/degradation		Does not change with time
Durability of compressive strength against ageing/degradation		Does not change with time

8. *Appropriate Technical Documentation and/or Specific Technical Documentation:*
Not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

Operations Director Susanne Bay Jensen
(name)

Randers
(place)

2021.03.15
(date of issue)

CE-marking

 1235
Leca Danmark A/S Randersvej 75 DK-8940 Randers SV 19 DoP_DK_16021000_EN 14063-1
EN 14063-1 16021000_EN 14063-1, Leca® 4-10 rund, Leca® Medium Intended use(s): Expanded clay lightweight aggregate for in-situ formed thermal insulation of ground floors
Declared performance: Thermal conductivity: 0,095 W/mK
Declaration of Performance and CE-marking to be found at www.leca.dk or sent on request.